1. Unique identification code of the product-type:	CU2/B		
2. Intended use/es:	Rectangular fire damper to be used in conjunction with partitions to maintain fire compartments in heating, ventilating and air conditioning installations.		
3. Manufacturer:	Rf-Technologies NV, Lange Ambachtstraat 40, B-9860 Oosterzele		
4. System/s of AVCP:	System 1		
<ol> <li>Harmonised standard / European Assessment Document; notified body / European Technical Assessment, Technical Assessment Body, notified body; certificate of constancy of performance:</li> </ol>	EN 15650:2010, BCCA with identification number 0749; BCCA-0749-CPR-BC1-606-0464-15650.03-0464&2517		
6. Declared performance according to EN 15650:2010	(Fire resistance according to EN 1366-2 and classifications according to EN 13501-3)		
Essential characteristics		Performance	

Essential characteristics			Performance		
Range	Туре	Wall	Sealing	Installation	Classification
$CU2/B \le 4 \text{ x CU2 } (200\text{x}200 \text{ mm} \le CU2 \le 1200\text{x}800 \text{ mm})$	Rigid wall	Reinforced concrete ≥ 110 mm	Mortar	1	El 120 (v <sub>e</sub> i ↔ o) S - (500 Pa)
CU2/B ≤ 4 x CU2 (200x200 mm ≤ CU2 ≤ 1500x800 mm)	Rigid wall	Reinforced concrete ≥ 110 mm	Mortar	1	El 60 (v <sub>e</sub> i ↔ o) S - (500 Pa)
				1	El 120 (v <sub>e</sub> i ↔ o) S - (300 Pa)

1 Type of installation: built-in 0/180° (B22, B21, B12)

	1	
B22	B21	B12

N. J. J. St. St. St. St. St. St. St. St. St. St	
Nominal activation conditions/sensitivity:	Pass
Response delay (response time): closure time	Pass
Operational reliability: cycling	CFTH - 50 cycles; MANO - 300 cycles; B(L)F(T) - 10000 cycles; BFL(T) - 10000 cycles; BFN(T) - 10000 cycles; ONE - 10000 cycles; ONE-X - 10000 cycles; UNIQ - 10000 cycles
Durability of response delay:	Pass
Durability of operational reliability:	Pass
Protection against corrosion according to EN 60068-2-52:	Pass
Damper casing leakage according to EN 1751:	≥ class B

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: Frank Verlinden, Head of Product Management



Oosterzele, 01/01/2024